

### ENERGY FIJI LIMITED

## SUPPLY AND DELIVERY OF PORTABLE

### HANDHELD GPS DATA COLLECTOR

### DEVICE

MR 391/2024

#### 1. Introduction and scope of work

Energy Fiji Limited (EFL) is responsible for generation, transmission and distribution of electricity in Viti Levu, Vanua Levu, Ovalau and Taveuni in Fiji. By January 2023, the EFL had 215,515 customers. This included residential, commercial and institutional customers.

EFL is requesting for proposals from reputable manufactures or suppliers for supply and delivery of a portable handheld GPS Data Collector device to be used for capturing the GPS coordinates and related information for updating the EFL GIS software.

This specification covers the general requirements for the supply and delivery of one (1) complete portable handheld GPS Data Collector device.

#### 2. General Requirements

The EFL's data capture team are required to take the GPS coordinates of EFL assets such as power poles, pillar boxes, transformers, underground cable routes, etc. and then manually enter additional information related to the asset being captured. This data is then transferred to a Windows based PC, processed and then used for updating the EFL GIS Software.

The portable handheld GPS Data Collector device must be supplied, complete with all accessories and software needed for its operation without the need of any additional attachments. The device must not require any periodical license renewal or updating of software at additional cost for use of the device.

The device must allow for customization of data entry fields for manual input of information such as pole type, pillar box type, pole dressing, cable type, transformer details and other information attributed to the asset being captured together with capturing of the GPS location of the asset.

EFL currently uses MapInfo Professional software as its GIS software. Bidders must provide a workflow of how information is to be transferred from the GPS Data Collector device ready for uploading onto MapInfo Professional software. The workflow must not rely on any third party software that needs to be purchased separately. If this cannot be avoided, then bidder must state with software(s) are required.

The Data Collector device must be of a rugged design, weatherproof, have a suitably sized sunlight readable display and be light weight.

### Bidders are required to fill in the Technical Particulars under Part B of Section 9. Appendix. This is a mandatory requirement.

#### 3. Details of Bidder

The bidder should be a manufacturer, authorized distributor or reseller of the device. The bidder must provide the following information:

- 1. Registered name of the bidder
- 2. Business address for correspondence (Location, Street, Locality City, Pin Code, Country, Telephone, Facsimile, Email, etc.).
- 3. Company Profile of device manufacturer and bidder (if authorized distributor or reseller).
- 4. Business registration details provided.
- 5. FRCS and FNPF certificate provided (For local bidders only).

#### 4. Information to be Supplied by Bidder

The Bidder is required to provide the following information as part of the proposal:

- 1. All relevant test reports and product standard.
- 2. Product specifications, detailed user manual and any calibration requirements.
- 3. Warranty on the product minimum 2 year full warranty required.
- 4. Method of replacement or reimbursement of faulty / defective or damaged device.
- 5. Lead time for supply of device.

- 6. Country of manufacture of the product with the brand / model etc.
- 7. Weight of the products.
- 8. Comment on the service life of the device.
- 9. Relevant manuals and instructions for proper care and handling of the device.
- 10. Quality management system used in manufacture of device.

The bidder is to include any other information that may be necessary or may add value to the product offered including any after sales service together with their bid submission such as technical support available to EFL to make better use of bidder's product.

#### 5. Training and Aftersales Service

Bidders must state if any form of training is required to use the device offered and to also comment on available aftersales service for repair, maintenance and proper operation of device offered.

#### 6. Packaging and Delivery

The successful bidder will be required to ship or hand deliver the device to EFL's Navutu Depot in Lautoka, Fiji Islands. All delivery costs must be included in the price offer. The device must be suitably packed to avoid any damages. EFL will not accept any package showing signs of damage that may have also caused damaged to the device.

#### 7. Price of Bid

Submission of bid must be in CIF incoterms. The bidder must provide currency of bid together with price under Part A of Section 9. Appendix. Price must remain valid for a period of minimum 90 days from the date of tender closing.

#### 8. Compliance to Specification

Bid submissions which do not comply with this specification will be rejected.

# 9. Appendix A. Price Schedule

Quantity	Item Description	Unit Price (CIF)	Currency of bid	Lead time for delivery
1	Portable handheld GPS Data Collector device			

#### B. Technical Particulars

Particulars	Requirement	Bidders Response
Name of	Bidder to state.	
manufacturer		
Place of	Bidder to state.	
manufacture		
Name of	Bidder to state.	
Device and		
Model number		
Accessories	Device must be	
provided	provided completed	
	with all accessories and	
	software needed for its	
	operation without the	
	need for any additional	
C	attachments.	
Certifications	Bidder to state.	
to which device		
complies to Environmental	ELL Dalla China Dalla	
Certifications	EU RoHS, China RoHS, REACH, WEEE, etc.	
Memory	Minimum 8GB RAM.	
Storage	Minimum 64GB,	
JUIAge	expandable via SD card.	
Processor	Minimum 64-bit guad-	
11000000	core.	
Software	Windows based -	
installed on	Windows 10 or above on	
Device and	device, Trimble Access.	
required on PC	Bidder to confirm	
for data	workflow for	
transfer and	transferring of data	
processing.	from the device to	
	Windows based PC and	
	ready for uploading to	
	MapInfo Professional	
	soft. Mention any	
	software required and	
	must be supplied with	
Software	device. Bidder to state.	
License	Diquer to state.	
requirements		
Display	Preferred display size of	
Display	5.5 to 7 inch	
	touchscreen display	
	with excellent	

resolution for crisp clear display. Sunlight readable, LED backlit, stylus pen provided. Display must be protected with hardened glass. Input and output ports (USB ports, connections) ports for data transfer, charger ports, clear entry in Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done. Battery Battery Battery Battery fife cycle battery can be charged and discharged before needing replacement. Battery Must connect to single Charger Battery Battery Must connect to single Charger Battery Hife dider to comment on number of times battery can be charged and discharged before needing replacement. Battery Must connect to single Charger Keyboard Hift functuded in device - provided. Keyboard Hift functuded in device - previde dide in Verice. Device must allow for quick charging of battery. Battery Must connect to single Charger with be provided. Also comment if device can be charged and 12V sockets typically found in Vehicles and Wattage requirement. Keyboard Hift accurate within ± Device Must not require any Dist a connectivity for Device must not require any Data connectivity for Device must not require any Data connectivity for Device must of sensor, Bensors Accelerometer, magnetic sensor,			
readable, LED backlit, stylus per provided. Display must be protected with hardened glass.         Input and output, ports (USB ports, connections of data is to be transfer, charger ports.         otputs for data transfer, charger ports.         bata entry in Data entry in Device         Data entry in Device         Battery         Capable of full day operation, hot swappable battery to provided with device. Device must allow for quick charging of battery.         Battery         Capable of full day operation, hot swappable battery to be provided with device. Device must allow for quick charging of battery.         Battery life cycle         Battery         Must connect to single Charger must be provided.         Battery on customization of fields for data entry to be provided with device. Device must allow for quick charging of battery.         Battery life cycle       Bidder to comment on number of times battery can be charged and discharged before needing replacement.         Battery       Must connect to single Charger         Charger       Provided Jower outlet. Charger must be provided.         provided       Also conment if device can be charged via 12V sockets typically found in Vehicles and Wattage reguirement.         Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of Pevice       Usi GNSS. The device querter on, Device         Operation of Device       Jisa Connectivity for operation		resolution for crisp	
stylus pen provided.         Dipplay must be protected with hardened glass.         Input and Bidder to state in detail output ports;         data is to be transfer;         ports for data is to be transfer;         transfer;         charger ports;         based computer.         etc.)         Data entry in Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done.         Battery       Capable of full day operation, hot swapable battery to be provided with device. Device must allow for quick charging of battery.         Battery       Spare battery to be provided with device. Device must allow for quick charging of battery.         Battery life       Bidder to comment on number of times battery.         Spare battery to be provided before needing replacement.         Battery       Must connect to single charged and discharged before can be charged and discharged before can be charged and dower outlet. Charger must be provided.         Also comment if device can be charged and power outlet. Charger must be provided.         Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of Highly accurate within ± Device       0.5m         Operation of Device       0.5m         Operation of Device       0.5m         Operation of Device       0.5m         Operat			
Display must be protected with hardened glass.           Input and output ports (USB ports, connections ports for data transfer, charger ports, etc.)         Bidder to state in detail all input and output data is to be transferred to Widows data is to be transferred to Widows transferred to Widows data entry for manual input of manual input of manual input of manual input of manual input of manual input of provided details of how this will be done.           Battery         Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.           Battery life cycle         Bidder to comment on number of times battery can be charged and discharged before needing replacement.           Battery         Must connect to single Charger           Charger         Sold Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V socket stypically found in Vehicles and Wattage requirement.           Keyboard         If included in device - preferred QWERTY with backlight.           Accuracy of Device         Highly accurate within ± Device           Operation of Device         0.5m           Operation of Device         0.5m			
protected with hardened glass.           Input and output ports (USB ports, connections ports for data transfer, transfer, transfer, transfer, transfered to Widows charger ports, transferred to Widows charger ports, transferred to Widows charger ports, transferred to Widows customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done.           Battery         Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done.           Battery         Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.           Battery life         Bidder to comment on number of times battery can be charged and discharged before needing replacement.           Battery         Guage data fill evice can be charged via 12V sockets typically found in Vehicles and Wattage requirement.           Keyboard         If included in device 0.5m           Provided         Highly accurate within ± backlight.           Accuracy of Device         Highly accurate within ± backlight.			
hardened glass.           Input and output ports output ports (USB ports, connections ports for data transfer, charger ports, etc.)         Bidder to state in detail dati is to be transferred to Widows data is to be transferred to Widows data entry for manual input of information. Bidder to provide details of how this will be done.           Battery         Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done.           Battery         Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.           Battery         Bidder to comment on number of times battery.           Battery         Bidder to comment on number of times battery.           Battery         Bidder to comment on number of times battery.           Battery         Must connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment. if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.           Keyboard         If included in device - preferred QWERTY with backlight.           Accuracy of Device         Via GNSS. The device on cancet within ± backlight.           Cearber operation.         Osm           Operation of Device         Via CMSS. The device operation.			
Input and Bidder to state in detail all input and output ports (USB ports, connections ports for data is to be transfer, transferred to Widows based computer. etc.) Device must allow Device for data entry for manual input of information. Bidder to provide details of how this will be done. Battery Capable of full day operation, hot swapable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery. Battery USE Bidder to comment on number of times will be done. Battery life Bidder to comment on number of times for additional discharged before needing replacement. Reyboard If full day sockets typically found in Vehicles and Wattage requirement. Keyboard If finculed in device of the scalar of the device of the provided. Also comment if device can be charged and discharged before needing replacement. Keyboard If finculed in device of the provided. Also comment to the vice on the charged via 12V sockets typically found in Vehicles and Wattage requirement. Keyboard If included in device of 0.5m Operation of Via GNS5. The device on the trequire any Data connectivity for operation. Accelerometer, the contert on the provided and the vice of the set of the operation. Battery to the proference of the set of the operation. Accelerometer, the contert of the operation. Battery the proference of 0.5m Operation of Via GNS5. The device of 0.5m Operation. Sensors Accelerometer, the		protected with	
output ports (USB ports, connections ports for data transfer, charger ports, etc.)       all input and output data is to be transferred to Widows data is to be transferred to Widows based computer.         Data entry in Data entry in Device       Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done.         Battery       Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.         Battery life cycle       Bidder to comment on number of times battery can be charged and discharged before needing replacement.         Battery       Must connect to single provided. Xustralian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.         Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of Device       Highly accurate within ± Device         Operation of Device       Wia KOSS. The device nust and require any Data connectivity for operation.		hardened glass.	
(USB ports, connections ports for data is to be transferred to Widows based computer. etc.)       based computer.         Data entry in Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done.       modelse for the second secon	Input and	Bidder to state in detail	
(USB ports, connections ports for data is to be transferred to Widows based computer. etc.)       based computer.         Data entry in Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done.       modelse for the second secon	output ports	all input and output	
connections device. Specify how data is to be transfer; transfer; transfer; based computer. etc.) Data entry in Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done. Battery Capable of full day operation, hot swapable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery. Battery life Bidder to comment on number of times battery cabe battery to be provided with device. Device must allow for quick charging of battery. Battery life Phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V socket stypically found in Vehicles and Wattage requirement. Keyboard If fincluded in device - 0.5m Operation of Via GNSS. The device - 0.5m Operation.	(USB ports,		
ports for data transfer, charger ports, etc.) Data entry in Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done. Battery Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery. Battery Battery Battery Battery Battery Battery Battery Must connent on number of times battery can be charged and discharged before needing replacement. Battery Charger phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device - can be charged via 12V sockets typically found in Vehicles and Wattage requirement. Keyboard I fincluded in device - preferred QWERTY with backlight. Accuracy of Via GNSS. The device Device Operation, of Via GNSS. The device operation. Sensors Accelerometer,			
transfer, transferred to Widows based computer. dcc.) Data entry in Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done. Battery Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery. Battery life Cycle Battery Battery mumber of times battery can be charged and discharged before needing replacement. Battery Charger Charger Charger Charger potset typically found in Vehicles and Wattage requirement. Keyboard If included in device - preferred QWERTY with backlight. Accelarometer, Sensors Accelarometer, Sensors Accelarometer,	ports for data		
charger ports, etc.) Data entry in Device Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done. Battery Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery. Battery life cycle Bidder to comment on number of times battery can be charged and discharged before needing replacement. Battery Must connect to single Charger phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device - preferred QWERTY with backlight. Accuracy of Highly accurate within ± Device 0.5m Operation of Via GNSS. The device must not require any Data connectivity for operation.			
etc.) Data entry in Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done. Battery Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery. Battery life cycle mumber of times battery can be charged and discharged before needing replacement. Battery Must connect to single Charger phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device - preferred QWERTY with backlight. Accuracy of Device Wia GNSS. The device must ont require any Data connectivity for operation. Sensors Accelerometer,			
Data entry in Device     Device must allow customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done.       Battery     Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.       Battery life     Bidder to comment on oumber of times battery can be charged and discharged before needing replacement.       Battery     Must connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger       Battery     Must connect to single provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.       Keyboard     If included in device - preferred QWERTY with backlight.       Accuracy of Operation of Device     If included in device - preferred QUERTY with backlight.       Accuracy of Device     Highly accurate within ± Device       Operation of Device     Via GNSS. The device must bor operation.       Sensors     Accelerometer,		bused computer.	
Device       customization of fields for data entry for manual input of information. Bidder to provide details of how this will be done.         Battery       Capable of full day operation, hot swappable battery to extend operating time. Spare battery to provided with device. Device must allow for quick charging of battery.         Battery life       Bidder to comment on number of times battery can be charged and discharged before needing replacement.         Battery       Must connect to single Charger         Phase 240V AC (± 5%) 50HZ Australian standard power outlet. Charger must be provided.         Also comment if device can be charged via 12V socket stypically found in Vehicles and Wattage requirement.         Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of Deration of Device       Via GNSS. The device must be preferred QUERTY with backlight.         Accuracy of Device       Highly accurate within ± Device         Sensors       Accelerometer,	,	Device must allow	
for data entry for manual input of information. Bidder to provide details of how this will be done.         Battery       Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.         Battery life       Bidder to comment on number of times battery can be charged and discharged before needing replacement.         Battery       Must connect to single Charger         Charger       phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided.         Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.         Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of Device       Highly accurate within ± Device         Operation of Device       Via GNSS. The device poreation.         Sensors       Accelerometer,			
manual input of information. Bidder to provide details of how this will be done.BatteryCapable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.Battery life cycleBidder to comment on number of times battery can be charged and discharged before needing replacement.BatteryBidder to comment on number of times battery can be charged and discharged before needing replacement.BatteryMust connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± Device must not require any Data connectivity for operation.SensorsAccelerometer,			
information. Bidder to provide details of how this will be done.         Battery       Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.         Battery life       Bidder to comment on number of times battery can be charged and discharged before needing replacement.         Battery       Must connect to single Charger         Charger       phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.         Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of Deration of       Highly accurate within ± Device         Operation of Device       Osmo         Sensors       Accelerometer,		-	
provide details of how this will be done.         Battery       Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.         Battery life       Bidder to comment on ounder of times battery can be charged and discharged before needing replacement.         Battery       Must connect to single charger         Charger       phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided.         Adso comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.         Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of Device       If sincluded in device - preferred QWERTY with backlight.         Accuracy of Device       Usin GNSS. The device must not require any Data connectivity for operation.         Sensors       Accelerometer,			
Attery       Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provide with device. Device must allow for quick charging of battery.         Battery life cycle       Bidder to comment on number of times battery can be charged and discharged before needing replacement.         Battery       Must connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger         Battery       Must connect to single provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.         Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of Device       Highly accurate within ± Device         Operation of Device       0.5m         Sensors       Accelerometer,			
Battery       Capable of full day operation, hot swappable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.         Battery life cycle       Bidder to comment on number of times battery can be charged and discharged before needing replacement.         Battery       Must connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger         Battery       Must connect to single provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.         Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of Device       Highly accurate within ± 0.5m         Operation of Device       Via GNSS. The device must not require any Data connectivity for operation.         Sensors       Accelerometer,		•	
operation, hotswappable battery toextend operating time.Spare battery to beprovided with device.Device must allow forquick charging ofbattery.Battery lifecycleand discharged beforeneeding replacement.BatteryBatteryMust connect to singleChargerphase 240V AC (± 5%)50Hz Australianstandard power outlet.Chargerprovided.Also comment if devicecan be charged via 12Vsockets typically foundin Vehicles and Wattagerequirement.KeyboardIf included in device -preferred QWERTY withbacklight.Accuracy ofHighly accurate within ±Device0.5mOperation ofVia GNSS. The deviceprevicenust not require anyData connectivity foroperation.SensorsAccelerometer,	Datta		
swapable battery to extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.Battery life cycleBidder to comment on number of times battery can be charged and discharged before needing replacement.BatteryMust connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment.BatteryMust connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± DeviceOperation of DeviceVia GNSS. The device operation.SensorsAccelerometer,	Battery		
extend operating time. Spare battery to be provided with device. Device must allow for quick charging of battery.Battery life cycleBidder to comment on number of times battery can be charged and discharged before needing replacement.BatteryMust connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± DeviceDevice0.5mOperation of DeviceVia GNSS. The device operation.SensorsAccelerometer,			
Spare battery to be provided with device. Device must allow for quick charging of battery.         Battery life cycle       Bidder to comment on number of times battery can be charged and discharged before needing replacement.         Battery       Must connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger         Battery       Must connect to single provided.         Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.         Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of Device       Highly accurate within ± Device         Operation of Device       Via GNSS. The device must not require any Data connectivity for operation.			
provided with device. Device must allow for quick charging of battery.Battery life cycleBidder to comment on number of times battery can be charged and discharged before needing replacement.Battery ChargerMust connect to single 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,			
Device must allow for quick charging of battery.Battery life cycleBidder to comment on number of times battery can be charged and discharged before needing replacement.Battery ChargerMust connect to single DHA Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± DeviceOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,			
quick charging of battery.Battery life cycleBidder to comment on number of times battery can be charged and discharged before needing replacement.Battery BatteryMust connect to single SOHz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device operation.SensorsAccelerometer,			
battery.Battery life cycleBidder to comment on number of times battery can be charged and discharged before needing replacement.Battery ChargerMust connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device 0.5mSensorsAccelerometer,			
Battery life cycle       Bidder to comment on number of times battery can be charged and discharged before needing replacement.         Battery       Must connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.         Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of Device       Highly accurate within ± 0.5m         Operation of Device       Via GNSS. The device nust not require any Data connectivity for operation.         Sensors       Accelerometer,		quick charging of	
cycle number of times battery can be charged and discharged before needing replacement. Battery Must connect to single Charger phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement. Keyboard If included in device - preferred QWERTY with backlight. Accuracy of Device 0.5m Operation of Device must not require any Data connectivity for operation.			
battery can be charged and discharged before needing replacement.BatteryMust connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,	Battery life	Bidder to comment on	
and discharged before needing replacement.BatteryMust connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,	cycle	number of times	
needing replacement.BatteryMust connect to single phase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,		battery can be charged	
Battery       Must connect to single         Charger       phase 240V AC (± 5%)         50Hz Australian         standard power outlet.         Charger must be         provided.         Also comment if device         can be charged via 12V         sockets typically found         in Vehicles and Wattage         requirement.         Keyboard       If included in device -         preferred QWERTY with         backlight.         Accuracy of       Highly accurate within ±         Device       0.5m         Operation of       Via GNSS. The device         Device       must not require any         Data connectivity for       operation.         Sensors       Accelerometer,		and discharged before	
Battery       Must connect to single         Charger       phase 240V AC (± 5%)         50Hz Australian         standard power outlet.         Charger must be         provided.         Also comment if device         can be charged via 12V         sockets typically found         in Vehicles and Wattage         requirement.         Keyboard       If included in device -         preferred QWERTY with         backlight.         Accuracy of       Highly accurate within ±         Device       0.5m         Operation of       Via GNSS. The device         Device       must not require any         Data connectivity for       operation.         Sensors       Accelerometer,		needing replacement.	
Chargerphase 240V AC (± 5%) 50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,	Battery		
50Hz Australian standard power outlet. Charger must be provided. Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,			
standard power outlet. Charger must be provided.Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,	5-		
Charger must be provided.Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,			
provided.Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy ofHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,			
Also comment if device can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,			
can be charged via 12V sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,			
sockets typically found in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy ofHighly accurate within ± 0.5mOperation ofVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,			
in Vehicles and Wattage requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy ofHighly accurate within ± DeviceOperation ofVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,		3	
requirement.KeyboardIf included in device - preferred QWERTY with backlight.Accuracy ofHighly accurate within ± DeviceOperation ofVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,			
Keyboard       If included in device - preferred QWERTY with backlight.         Accuracy of       Highly accurate within ±         Device       0.5m         Operation of       Via GNSS. The device         Device       must not require any Data connectivity for operation.         Sensors       Accelerometer,		-	
preferred QWERTY with backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,	Kayboard		
backlight.Accuracy of DeviceHighly accurate within ± 0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,	reyboard		
Accuracy of Device       Highly accurate within ± 0.5m         Operation of Device       Via GNSS. The device must not require any Data connectivity for operation.         Sensors       Accelerometer,		•	
Device0.5mOperation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,	A		
Operation of DeviceVia GNSS. The device must not require any Data connectivity for operation.SensorsAccelerometer,			
Device must not require any Data connectivity for operation. Sensors Accelerometer,			
Data connectivity for operation.       Sensors       Accelerometer,			
operation.           Sensors         Accelerometer,	Device		
Sensors Accelerometer,			
	-		
magnetic sensor,	Sensors		
		magnetic sensor,	

	ambient light sensor,	
	proximity sensor.	
Material of	Must be rugged design	
Device and IP	with drop protection,	
Rating	meet IP 68 rating.	
-		
Device	Bidder to state.	
dimensions		
and weight		
Device	Minimum 2 year full	
Warranty	warranty required.	
	Method of replacement	
	or reimbursement of	
	faulty / defective or	
	damaged device.	
Training	Bidder will have to	
requirement	specific if any form of	
	training is required for	
	use of the device.	
	Provide details on after	
	sales service for repair,	
	maintenance and	
	proper operation of	
	device.	
Calibration	Bidder must provide	
requirement	details of any periodical	
	calibration requirement	
	for proper operation of	
	the device.	
Number of	Bidder to state.	
years Device		
has been in		
production		
Number of	Bidder to state.	
years		
Manufacturer		
and bidder has		
been in		
business		

Name of Bidder: \_\_\_\_\_

Signature of Bidder: \_\_\_\_\_

Date: \_\_\_\_\_

Email: \_\_\_\_\_

Company Stamp:

### **TENDER CHECKLIST**

The Bidders must ensure that the details and documentation mention below must
be submitted as part of their tender Bid

Teı	nder Number
Tei	nder Name
1.	Full Company / Business Name:
	(Attach copy of Registration Certificate)
2.	Director/Owner(s):
3.	Postal Address:
4.	Phone Contact:
5.	Fax Number:
6.	Email address:
7.	Office Location:
8.	TIN Number:
9.	FNPF Employer Registration Number: (For Local Bidders only) (Mandatory)
10.	Provide a copy of Valid FNPF Compliance Certificate (Mandatory- Local Bidders only)
11. onl	Provide a copy of Valid FRCS (Tax) Compliance Certificate (Mandatory Local Bidders $\mathbf{y}$ )
12.	Provide a copy of Valid FNU Compliance Certificate (Mandatory Local Bidders only)
13.	Contact Person:
	I declare that all the above information is correct.
	Name:
	Position:
	Sign:
	Date:

#### **Tender Submission - Instruction to Bidders**

Bidders are requested to upload electronic copies via Tender Link by registering their interest at: <u>https://www.tenderlink.com/efl</u>

EFL will not accept any hard copy submission to be dropped in the tender box at EFL Head Office in Suva.

This tender closes at 4.00pm (1600hrs) on Wednesday 11<sup>th</sup> December, 2024.

For further information or clarification please contact our Supply Chain Office on phone (+679) 3224360 or (+679) 9992400 or email us on <u>tenders@efl.com.fj</u>

The bidders must ensure that their bid is inclusive of all Taxes payable under Fiji Income Tax Act. Bidders are to clearly state the percentage of VAT that is applicable to the bid prices.

The lowest bid will not necessarily be accepted as the successful bid.

The Tender Bids particularly the "Price" must be typed and not hand written.

Any request for the extension of the closing date must be addressed to EFL in writing three (3) working days prior to the tender closing date.

Tender Submission via email or fax will not be accepted.